Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-964-7620

Cross Sec	tional Shape:
Round	
Thread Cla	ass:
3b 1st end	
Thread Dir	rection:
Right-hand	1st end
Inside Dia	
0.625 inche	es estatution and the second se
Tempuratu	ire Rating:
	ees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Di	
0.781 inche	€S
Connectio	n Style:
	flare 1st end
End Conne	ection Design:
Straight 1st	tend
Connectio	n Type:
Threaded in	nternal tube 1st end
Features F	Provided:
Electrostati	c discharge capability
Thready Q	ty Per Inch (tpi):
20 1st end	
Burst Test	Pressure:
6000.0 pou	inds per square inch
Layer Com	nposition And Location:
Outer layer	braided corrosion resistant steel wire
Maximum	Operating Pressure:
1000.0 pou	inds per square inch
Thread Siz	ie:
1.062 inche	es 1st end
Seat Angle	):
37.0 degre	es 1st end
Inside Sur	face Condition:
Smooth	
Measuring	Method And Length:
30.000 incl	nes working
Thread Se	ries Designator:
Un 1st end	
Shelf Life:	
N/a	
Unit Of Me	asure:

## NSN 4720-00-964-7620

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

