## NSN 4720-00-966-2232

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-966-2232 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.312 inches **Minimum Inside Bending Radius:** 2.000 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer molded polytetrafluoroethylene **Maximum Operating Pressure:** 100.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end **Vacuum In Torr:** 

50.8

**Inside Surface Condition:** 

Smooth

## NSN 4720-00-966-2232

Nonmetallic Hose Assembly - Page 2 of 2



| Measuring Method And Le | enath: |
|-------------------------|--------|
|-------------------------|--------|

8.250 inches working and 8.500 inches working

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0