NSN 4720-00-966-2240

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-966-2240

Crass Sectional Shape
Cross Sectional Shape: Round
Thread Class:
3b 1st end Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Exterior Color:
Natural Para Control of the Control
Angle Between Rigid Elbow Fittings In Deg:
38.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 2nd end
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.250 inches working and 19.750 inches working
Special Features:

Furnished w/plastic, polytetrafluoroethylene, ams3653, chafing sleeve, 8.750 in. Min, 9.000 in. Maximum lg, at end w/90.0 degrees fitting; media spec: fuel, mil-f-5624 and mil-f-5161

NSN 4720-00-966-2240

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Design	₽d	
------------------------	----	--

Fuel single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0