Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-967-3120

ross Sectional Shape: ound hread Class: b 1st end
hread Class:
a fot and
hread Direction:
ight-hand 1st end
side Diameter:
312 inches
empurature Rating:
0.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
utside Diameter:
438 inches
inimum Inside Bending Radius:
000 inches
onnection Style:
wivel nut, inverted flare 1st end
nd Connection Design:
traight 1st end
onnection Type:
hreaded internal tube 1st end
hready Qty Per Inch (tpi):
8 1st end
urst Test Pressure:
000.0 pounds per square inch
ayer Composition And Location:
uter layer rubber impregnated braided steel wire
aximum Operating Pressure:
000.0 pounds per square inch
hread Size:
562 inches 1st end
eat Angle:
7.0 degrees 1st end
ydrostatic Test Pressure:
000.0 pounds per square inch
side Surface Condition:
mooth
leasuring Method And Length:
8.200 inches working
edia For Which Designed:
uel/oil, hydrocarbon single response
hread Series Designator:
nf 1st end

NSN 4720-00-967-3120

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

