Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-967-4199

Cross Sec	ctional Shape:
Round	
Thread Cl	ass:
3b 1st end	
Thread Di	rection:
Right-hand	1 1st end
Inside Dia	meter:
0.880 inch	es
Tempurat	ure Rating:
-40.0 degr	ees fahrenheit and 250.0 degrees fahrenheit single response
Outside D	iameter:
1.230 inch	es
Minimum	Inside Bending Radius:
7.375 inch	es
Exterior C	color:
Black	
Connectio	on Style:
Swivel nut	flare 1st end
End Conn	ection Design:
Straight 1s	st end
Connectio	on Type:
Threaded	internal tube 1st end
Features	Provided:
Reusable	end fittings
Thready C	Rty Per Inch (tpi):
12 1st end	
Burst Tes	t Pressure:
3200.0 po	unds per square inch
Layer Cor	nposition And Location:
1st layer b	raided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum	Operating Pressure:
800.0 pou	nds per square inch
Thread Si	ze:
1.312 inch	es 1st end
Seat Angl	e:
37.0 degre	es 1st end
Hydrostat	ic Test Pressure:
1600.0 po	unds per square inch
Outer Cov	vering Environmental Protection:
Abrasion r	esistant and weatherproof
Vacuum li	n Torr:
254.0	

NSN 4720-00-967-4199

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:

Smooth

Measuring Method And Length:

12.000 inches

Media For Which Designed:

Air and fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0