## NSN 4720-00-967-6332

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-967-6332 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.906 inches **Minimum Inside Bending Radius:** 6.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and mildew resistant and oil resistant **Vacuum In Torr:** 50.8

**Inside Surface Condition:** 

Smooth

## NSN 4720-00-967-6332

No Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
9.250 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon and water, fresh single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: