## NSN 4720-00-967-6335

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-967-6335

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.031 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
14 2nd end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant and oil resistant
Vacuum In Torr:
304.8
Inside Surface Condition:
Smooth

## NSN 4720-00-967-6335

**Fiig:** A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
7.875 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon and water, fresh single response
Thread Series Designator:
Uns 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No