NSN 4720-00-968-7152

Metallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-968-7152

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Outside Diameter:
0.766 inches
Minimum Inside Bending Radius:
4.000 inches
Inner Conveying Tube Style:
Interlocked unpacked
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Features Provided: Identical ends
Identical ends
Identical ends Layer Composition And Location:
Identical ends Layer Composition And Location: Outer layer braided steel wire
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure:
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size:
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length:
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator:
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life:
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life: N/a
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life: N/a
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure:
Identical ends Layer Composition And Location: Outer layer braided steel wire Maximum Operating Pressure: 750.0 pounds per square inch Thread Size: 0.750 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: