## NSN 4720-00-968-7218

Metallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-968-7218

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.313 inches  |
| Outside Diameter:   |
| 0.531 inches  |
| Minimum Inside Bending Radius:  |
| 2.500 inches  |
| Inner Conveying Tube Style:   |
| Interlocked unpacked  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
|   |
| Features Provided:  |
| Features Provided: Identical ends   |
|   |
| Identical ends  |
| Identical ends  Layer Composition And Location:   |
| Identical ends  Layer Composition And Location:  Outer layer braided steel wire   |
| Identical ends  Layer Composition And Location:  Outer layer braided steel wire  Maximum Operating Pressure:  |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch   |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size:  |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size: 0.500 inches 1st end   |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch  Thread Size: 0.500 inches 1st end  Measuring Method And Length:  |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 48.000 inches  |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator:  |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end  |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life:  |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch  Thread Size: 0.500 inches 1st end  Measuring Method And Length: 48.000 inches  Thread Series Designator: Unf 1st end  Shelf Life: N/a                                |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch  Thread Size: 0.500 inches 1st end  Measuring Method And Length: 48.000 inches  Thread Series Designator: Unf 1st end  Shelf Life: N/a                                |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure:                   |
| Identical ends  Layer Composition And Location: Outer layer braided steel wire  Maximum Operating Pressure: 1200.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 48.000 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: |