

View Online at <https://aerobasegroup.com/nsn/4720-00-972-8109>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.312 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.680 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

9000.0 pounds per square inch

**First End Swivel Action Capability:**

Included

**Layer Composition And Location:**

Outer layer rubber impregnated braided cotton cord err-100

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

0.625 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch

**Vacuum In Torr:**

50.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

8.875 inches

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Water single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0