

View Online at <https://aerobasegroup.com/nsn/4720-00-972-8671>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response

**Outside Diameter:**

0.562 inches

**Exterior Color:**

Black

**Hose Or Tubing Specification/std Data:**

Sae j1401-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Swivel nut, inverted flare 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium 1st end

**Connection Type:**

Threaded external tube 2nd end

**Thready Qty Per Inch (tpi):**

24 2nd end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

4500.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer rubber impregnated braided cotton cord err-100 or 1st layer rubber impregnated braided rayon cord err-100

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

45.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Cold resistant and ozone resistant and salt water resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

21.500 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Brake fluid, nonmineral oil single response

**Thread Series Designator:**

Uns 2nd end

**Specification Data:**

Sae j1401-81343 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0