

View Online at <https://aerobasegroup.com/nsn/4720-00-972-8671>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-65.0 degrees fahrenheit single response

Outside Diameter:

0.562 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j1401-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

24 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

4500.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord err-100 or 1st layer rubber impregnated braided rayon cord err-100

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Cold resistant and ozone resistant and salt water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.500 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Brake fluid, nonmineral oil single response

Thread Series Designator:

Uns 2nd end

Specification Data:

Sae j1401-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0