

View Online at <https://aerobasegroup.com/nsn/4720-00-974-8208>

Cross Sectional Shape:

Round

Inside Diameter:

0.880 inches

Flange Thickness:

0.187 inches 2nd end and 0.218 inches 2nd end

Outside Diameter:

1.110 inches

Center To Center Distance Between Bolt Holes Along Width:

1.414 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.414 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.000 inches 2nd end and 2.180 inches 2nd end

Flange Width:

2.000 inches 2nd end and 2.180 inches 2nd end

Connection Style:

Raised 2nd end

Bolt Hole Diameter:

0.274 inches 2nd end and 0.288 inches 2nd end

Raised Face Height:

0.010 inches 1st end and 0.020 inches 1st end

Raised Face Diameter:

1.495 inches 2nd end and 1.500 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided steel wire

Maximum Operating Pressure:

500.0 pounds per square inch

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.760 inches working and 20.000 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Hose prebent to a fixed position and supplied w/six clamps

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0