Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-981-2687

Cross Sectional Shape:

Round

Inside Diameter:

0.500 inches

Tempurature Rating:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Outside Diameter:

0.922 inches

Minimum Inside Bending Radius:

5.005 inches

Connection Style:

Cam or lever (external) 1st end

End Connection Design:

Straight 1st end

Connection Type:

External quick disconnect 1st end

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord

Outer Covering Environmental Protection:

Hydraulic solution resistant and fuel resistant and oil resistant and water resistant and alcohol resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

240.000 inches and 252.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid and fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A542a0