NSN 4720-00-982-2133

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-982-2133

Outside Diameter:					
0.578 inches					
Minimum Inside Bending Radius:					
4.000 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
End Fitting Component And Material:					
Nut aluminum alloy 1st end					
Fitting Component And Surface Treatment:					
Nipple anodize all ends					
Connection Type:					
Threaded internal tube 1st end					
Second End Relationship With First End:					
Identical					
Burst Test Pressure:					
600.0 pounds per square inch					
First End Swivel Action Capability:					
Not included					
Layer Composition And Location:					
Outer layer braided cotton cord					
Thread Size:					
0.562 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Outer Covering Environmental Protection:					
Corrosion resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
180.000 inches working					
Special Features:					
Inner conveying tube material-rubber, synthetic					

NSN 4720-00-982-2133

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

88044-an6270-6-180 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0