## NSN 4720-00-982-3560

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-982-3560 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.672 inches **Connection Style:** Swivel nut with compression sleeve 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 35.5 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 18.000 inches **Thread Series Designator:** Unf 1st end Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 4720-00-982-3560

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0