NSN 4720-00-982-3613

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-982-3613

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 180.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Exterior Color:
Black
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
24.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.000 inches
Thread Series Designator:
Unf 1st end
Specification Data:
81205-bach30j060140 manufacturers source control
Shelf Life:
N/a

NSN 4720-00-982-3613

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0