NSN 4720-00-982-9375

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-982-9375 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.625 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.062 inches **Minimum Inside Bending Radius:** 8.000 inches **Exterior Color:** Black **Connection Style:** Flared 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 11000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2750.0 pounds per square inch **Thread Size:** 1.094 inches 2nd end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 5500.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant **Inside Surface Condition:**

Smooth

Measuring Method And Length:

30.500 inches

NSN 4720-00-982-9375

Nonmetallic Hose Assembly - Page 2 of 2



Me	dia	For	Which	Design	ed:

Hydraulic fluid single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0