## NSN 4720-00-983-2849

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-983-2849

Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 0.750 inches and 0.812 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Factures Dravided
Features Provided:
Electrostatic discharge capability
Electrostatic discharge capability
Electrostatic discharge capability  Burst Test Pressure:
Electrostatic discharge capability <b>Burst Test Pressure:</b> 9000.0 pounds per square inch
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:  0.562 inches 1st end
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  37.0 degrees 1st end
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  37.0 degrees 1st end  Hydrostatic Test Pressure:
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  37.0 degrees 1st end  Hydrostatic Test Pressure:  4500.0 pounds per square inch
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  37.0 degrees 1st end  Hydrostatic Test Pressure:  4500.0 pounds per square inch  Outer Covering Environmental Protection:
Electrostatic discharge capability  Burst Test Pressure:  9000.0 pounds per square inch  Layer Composition And Location:  1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure:  2250.0 pounds per square inch  Thread Size:  0.562 inches 1st end  Seat Angle:  37.0 degrees 1st end  Hydrostatic Test Pressure:  4500.0 pounds per square inch  Outer Covering Environmental Protection:  Mildew resistant and oil resistant and oil resistant
Electrostatic discharge capability  Burst Test Pressure: 9000.0 pounds per square inch  Layer Composition And Location: 1st layer braided steel wire and outer layer molded rubber, chloroprene  Maximum Operating Pressure: 2250.0 pounds per square inch  Thread Size: 0.562 inches 1st end  Seat Angle: 37.0 degrees 1st end  Hydrostatic Test Pressure: 4500.0 pounds per square inch  Outer Covering Environmental Protection: Mildew resistant and oil resistant and oil resistant Inside Surface Condition:

## NSN 4720-00-983-2849

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

SUPP-OR-TSH-ARNI

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0