

View Online at <https://aerobasegroup.com/nsn/4720-00-983-4291>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j1402 type b-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, compression 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Socket copper alloy 2nd end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene err-100

Maximum Operating Pressure:

225.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.500 inches

Second End Swivel Action Capability:

Not included

Seat Radius:

0.062 inches 1st end

Special Features:

Furnished with adapter, straight, pipe to tube

Thread Series Designator:

Unef 1st end

Specification Data:

Sae j1402 type b-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0