## NSN 4720-00-983-6036

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-983-6036

2b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.500 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response						
Outside Diameter:						
0.969 inches						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Thready Qty Per Inch (tpi):						
14 2nd end						
Burst Test Pressure:						
6000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
1750.0 pounds per square inch						
Thread Size:						
0.875 inches 2nd end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
3500.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Outer Covering Environmental Protection:						
Abrasion resistant and oil resistant						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
46.500 inches						
Media For Which Designed:						

Fuel/oil, hydrocarbon single response

## NSN 4720-00-983-6036

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Uns 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0