NSN 4720-00-984-3081

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-984-3081

| Round | | | | |
|---|--|--|--|--|
| Thread Class: | | | | |
| 3b 1st end | | | | |
| Thread Direction: | | | | |
| Right-hand 1st end | | | | |
| Inside Diameter: | | | | |
| 0.219 inches | | | | |
| Tempurature Rating: | | | | |
| -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response | | | | |
| Outside Diameter: | | | | |
| 0.438 inches | | | | |
| Minimum Inside Bending Radius: | | | | |
| 2.000 inches | | | | |
| Connection Style: | | | | |
| Swivel nut flare 1st end | | | | |
| End Connection Design: | | | | |
| Straight 1st end | | | | |
| Connection Type: | | | | |
| Threaded internal tube 1st end | | | | |
| Features Provided: | | | | |
| Electrostatic discharge capability | | | | |
| Burst Test Pressure: | | | | |
| 6000.0 pounds per square inch | | | | |
| Layer Composition And Location: | | | | |
| 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire | | | | |
| Maximum Operating Pressure: | | | | |
| 1000.0 pounds per square inch | | | | |
| Thread Size: | | | | |
| 0.438 inches 1st end | | | | |
| Seat Angle: | | | | |
| 37.0 degrees 1st end | | | | |
| Hydrostatic Test Pressure: | | | | |
| 3000.0 pounds per square inch | | | | |
| Outer Covering Environmental Protection: | | | | |
| Abrasion resistant and corrosion resistant | | | | |
| Inside Surface Condition: | | | | |
| Smooth | | | | |
| Measuring Method And Length: | | | | |
| 11.375 inches working | | | | |
| Media For Which Designed: | | | | |
| Air and fuel/oil, hydrocarbon single response | | | | |

NSN 4720-00-984-3081

Nonmetallic Hose Assembly - Page 2 of 2



| | | • | | |
|----|------|--------|--------|--------|
| Ιh | read | Series | Desiar | າator: |
| | | | | |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0