## NSN 4720-00-986-1440

**Cross Sectional Shape:** 

Thread Direction:
Right-hand 1st end
Inside Diameter:

**Tempurature Rating:** 

**Outside Diameter:** 

1.500 inches

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-986-1440

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

2.062 inches
Minimum Inside Bending Radius:
14.000 inches
Exterior Color:
Red
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded external hose 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
600.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spirally laid cord strands err-100
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
1.500 inches 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.000 inches
Special Features:
Inner conveying tube material-rubber, buna-n

## NSN 4720-00-986-1440

Nonmetallic Hose Assembly - Page 2 of 2



_	brood	Carias	Docimotori
ı	meau	oenes	Designator:

Npsh 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0