

View Online at <https://aerobasegroup.com/nsn/4720-00-986-9681>

Cross Sectional Shape:

Round

Inside Diameter:

0.750 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.265 inches 1st end

Outside Diameter:

1.188 inches

Minimum Inside Bending Radius:

9.500 inches

Angle Between Rigid Elbow Fittings In Deg:

231.0

Flange Outside Diameter:

1.500 inches 1st end

Connection Style:

Plain 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided cotton cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1250.0 pounds per square inch

Flow Angle:

60.0 degrees 1st end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.500 inches working

Flange Style:

Round w/ out bolt holes 1st end

Special Features:

End connections are flange heads

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0