Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-987-3657

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 225.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.422 inches |
| Minimum Inside Bending Radius: |
| 2.250 inches |
| End Application: |
| Grumman a10 aircraft |
| Connection Style: |
| Plain 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded external tube 1st end |
| Burst Test Pressure: |
| 1600.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fabric and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 400.0 pounds per square inch |
| Thread Size: |
| 0.500 inches 1st end |
| Seat Angle: |
| 45.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Fuel resistant and oil resistant and mildew resistant and ozone resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 20.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 1st end |
| |

NSN 4720-00-987-3657

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

