

View Online at <https://aerobasegroup.com/nsn/4720-00-987-3941>

Cross Sectional Shape:

Round

Inside Diameter:

1.812 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.188 inches 1st end

Outside Diameter:

2.153 inches

Minimum Inside Bending Radius:

17.000 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

300.0

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

3.000 inches 1st end

Flange Width:

3.000 inches 1st end

Connection Style:

Raised swivel 1st end

Bolt Hole Diameter:

0.328 inches 1st end

Raised Face Height:

0.013 inches 1st end

Raised Face Diameter:

2.750 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Raised face flange 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Burst Test Pressure:

640.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

120.0 pounds per square inch

Hydrostatic Test Pressure:

240.0 pounds per square inch

Flow Angle:

45.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.350 inches working

Flange Style:

Rectangular (includes square) 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0