NSN 4720-00-988-1102

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-00-988-1102 | |
|---|--|
| Cross Sectional Shape: | |
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.188 inches | |
| Tempurature Rating: | |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.312 inches | |
| Minimum Inside Bending Radius: | |
| 2.000 inches | |
| Connection Style: | |
| Swivel nut flare 2nd end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Thready Qty Per Inch (tpi): | |
| 20 2nd end | |
| Burst Test Pressure: | |
| 12000.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer braided corrosion resistant steel wire | |
| Maximum Operating Pressure: | |
| 1500.0 pounds per square inch | |
| Thread Size: | |
| 0.438 inches 1st end | |
| Seat Angle: | |
| 37.0 degrees 2nd end | |
| Hydrostatic Test Pressure: | |
| 3000.0 pounds per square inch | |

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-00-988-1102

Nonmetallic Hose Assembly - Page 2 of 2



| Thread S | Series | Designator: |
|----------|--------|-------------|
|----------|--------|-------------|

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0