## NSN 4720-00-989-0102

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-989-0102 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord **Maximum Operating Pressure:** 400.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 800.0 pounds per square inch **Outer Covering Environmental Protection:** Fuel resistant and oil resistant and mildew resistant and cold resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 35.750 inches **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 4720-00-989-0102

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0