Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-989-4789

| Cross Sectional Shape:<br>Round<br>Inside Diameter:<br>0.375 inches<br>Outside Diameter:<br>0.688 inches<br>Connection Style:<br>Swivel nut, compression 1st end<br>End Connection Design:<br>Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch<br>Measuring Method And Length: |
|---|
| Inside Diameter:<br>0.375 inches<br>Outside Diameter:<br>0.688 inches<br>Connection Style:<br>Swivel nut, compression 1st end<br>End Connection Design:<br>Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch  |
| 0.375 inches<br>Outside Diameter:<br>0.688 inches<br>Connection Style:<br>Swivel nut, compression 1st end<br>End Connection Design:<br>Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch  |
| Outside Diameter:0.688 inchesConnection Style:Swivel nut, compression 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal gas cylinder 1st endBurst Test Pressure:800.0 pounds per square inchMaximum Operating Pressure:200.0 pounds per square inch  |
| 0.688 inches<br>Connection Style:<br>Swivel nut, compression 1st end<br>End Connection Design:<br>Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| Connection Style:<br>Swivel nut, compression 1st end<br>End Connection Design:<br>Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| Swivel nut, compression 1st end<br>End Connection Design:<br>Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch  |
| End Connection Design:<br>Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| Straight 1st end<br>Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| Connection Type:<br>Threaded internal gas cylinder 1st end<br>Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| Threaded internal gas cylinder 1st end<br><b>Burst Test Pressure:</b><br>800.0 pounds per square inch<br><b>Maximum Operating Pressure:</b><br>200.0 pounds per square inch   |
| Burst Test Pressure:<br>800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| 800.0 pounds per square inch<br>Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| Maximum Operating Pressure:<br>200.0 pounds per square inch   |
| 200.0 pounds per square inch  |
|   |
| Measuring Method And Length:  |
|   |
| 21.500 inches working and 22.500 inches working   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A542a0  |