Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-989-5057

C-	oss Sectional Shape
	oss Sectional Shape:
	read Class:
	1st end
	read Direction:
	ght-hand 1st end
	side Diameter:
	105 inches
	mpurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	Itside Diameter:
	ngle Between Rigid Elbow Fittings In Deg:
-	
	onnection Style:
-	vivel nut flare 1st end
	d Connection Design:
	bow 1st end
	onnection Type:
	readed internal tube 1st end
	ready Qty Per Inch (tpi):
	1st end
	irst Test Pressure:
	00.0 pounds per square inch
	yer Composition And Location:
	iter layer braided corrosion resistant steel wire
	aximum Operating Pressure:
	00.0 pounds per square inch
Th	read Size:
0.8	375 inches 1st end
	at Angle:
37	.0 degrees 1st end
Hy	drostatic Test Pressure:
40	00.0 pounds per square inch
Flo	bw Angle:
90	.0 degrees 1st end
Οι	Iter Covering Environmental Protection:
Со	rrosion resistant
Va	cuum In Torr:
50	.8
Ins	side Surface Condition:
Sn	nooth



Measuring Method And Length:

8.125 inches working

Special Features:

PEND-IN-GUS-ERCO

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0