NSN 4720-00-989-6296

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-989-6296

| Round |
|--|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Outside Diameter: |
| 0.625 inches |
| Connection Style: |
| Swivel nut, flared 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded external hose 2nd end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 18 2nd end |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 2500.0 pounds per square inch |
| Thread Size: |
| 0.960 inches 1st end |
| Outer Covering Environmental Protection: |
| Abrasion resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 15.000 inches working |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Npt 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |