Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-990-2125

Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.688 inches	
Tempurature Rati	ng:
-65.0 degrees fahr	enheit and 200.0 degrees fahrenheit single response
Outside Diameter	
1.219 inches	
Minimum Inside E	ending Radius:
7.750 inches	
Connection Style	
Swivel nut, flarele	as 1st end
End Connection I	Design:
Straight 1st end	
Connection Type	
Threaded internal	ube 1st end
Thready Qty Per	nch (tpi):
12 1st end	
Burst Test Press	re:
12000.0 pounds po	r square inch
Layer Compositio	n And Location:
1st layer braided c	prrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene	
Maximum Operat	ng Pressure:
3000.0 pounds per	square inch
Thread Size:	
1.062 inches 1st e	nd
Seat Angle:	
12.0 degrees 1st e	nd
Hydrostatic Test	Pressure:
6000.0 pounds per	square inch
Outer Covering E	nvironmental Protection:
Abrasion resistant	and oil resistant
Inside Surface Co	ndition:
Smooth	
Measuring Metho	d And Length:
47.000 inches wo	king
Media For Which	Designed:
/	on single response

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unj 1st end

Specification Data:

96906-ms28762 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0