

View Online at <https://aerobasegroup.com/nsn/4720-00-990-3261>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Exterior Color:**

Black

**Connection Style:**

Inverted flare 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded external tube 2nd end

**Thready Qty Per Inch (tpi):**

18 2nd end

**Burst Test Pressure:**

4500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided rayon cord and 2nd layer braided rayon cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1125.0 pounds per square inch

**Thread Size:**

0.688 inches 2nd end

**Seat Angle:**

45.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

42.000 inches

**Special Features:**

Furnished w/a 7.750 in. Lg tube assembly, material steel, 1 flared nut on each end, this is connected to the tube fitting end of the hose

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Uns 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0