Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-990-5185

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Green
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer spirally laid corrosion resistant steel wire and outer layer braided polyamide cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
46.000 inches
Media For Which Designed:
Oxygen, gaseous single response
Thread Series Designator:
Unf 1st end

NSN 4720-00-990-5185

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

