## NSN 4720-00-990-6425

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-990-6425

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.187 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.515 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 2nd end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
96.000 inches working
Thread Series Designator:
Unf 2nd end
Fsc Application Data:
Hose assembly, nonmetallic, except fire fighting
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4720-00-990-6425

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0