

View Online at <https://aerobasegroup.com/nsn/4720-00-990-9063>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-60.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

3.750 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Perforated outer cover

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

225.0 pounds per square inch

Thread Size:

0.688 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant and ozone resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

70.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Specification Data:

81349-mil-h-3992 government specification

Specification Or Standard:

1 class and 1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-3992 spec.