## NSN 4720-00-991-8406

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Uns 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-991-8406

2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.844 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.880 inches and 20.120 inches
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:

## NSN 4720-00-991-8406

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0