Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-991-8866

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Tempurature Rating:

-67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response

Outside Diameter:

Connection Style:

0.500 inches

Minimum Inside Bending Radius:

4.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-5593, size 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil ms27404-4d standard (includes industry or association standards, individual manufactureer standards, etc.).

Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings Second End Relationship With First End: Identical **Burst Test Pressure:** 1250.0 pounds per square inch First End Swivel Action Capability: Included Layer Composition And Location: Outer layer molded rubber, synthetic err-100 First End Fitting/component And Material: Complete fitting, aluminum alloy, mil-a-38726 **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle:

37.0 degrees 1st end

NSN 4720-00-991-8866

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
400.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and oil resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
540.000 inches working
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Air single response
Thread Series Designator:
Unjf 1st end
Specification Data:
88044-an6270 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0
Mil-std (military Standard):
Mil-h-5593 spec.