## NSN 4720-00-992-1571

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-992-1571

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.851 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Bolt Circle Diameter:
1.312 inches 2nd end
Flange Thickness:
0.297 inches 2nd end
Outside Diameter:
1.140 inches
Minimum Inside Bending Radius:
7.300 inches
Bolt Hole Quantity:
4 2nd end
Flange Outside Diameter:
2.312 inches 2nd end
Connection Style:
Swivel nut flare 1st end
Bolt Hole Diameter:
0.205 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end

## NSN 4720-00-992-1571

Nonmetallic Hose Assembly - Page 2 of 2



Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
<b>Measuring Method And Length:</b>
10.338 inches
Flange Style:
Round w/ bolt holes 2nd end
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A542a0