

View Online at <https://aerobasegroup.com/nsn/4720-00-992-6343>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 0.431 inches and 0.463 inches

**Outside Diameter:**

Between 0.828 inches and 0.890 inches

**Minimum Inside Bending Radius:**

5.750 inches

**Quick Disconnect Size:**

0.568 inches 1st end

**Connection Style:**

Push (internal) 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Internal quick disconnect 1st end

**Burst Test Pressure:**

14000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

144.500 inches

**Special Features:**

Plug dust quick disconnect fasten by sash chain 2 required

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0