## NSN 4720-00-992-6343



Nonmetallic Hose Assembly - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/4720-00-992-6343 **Cross Sectional Shape:** Round **Inside Diameter:** Between 0.431 inches and 0.463 inches **Outside Diameter:** Between 0.828 inches and 0.890 inches **Minimum Inside Bending Radius:** 5.750 inches **Quick Disconnect Size:** 0.568 inches 1st end **Connection Style:** Push (internal) 1st end **End Connection Design:** Straight 1st end **Connection Type:** Internal quick disconnect 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber **Maximum Operating Pressure:** 3000.0 pounds per square inch **Hydrostatic Test Pressure:** 7000.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 144.500 inches **Special Features:** Plug dust quick disconnect fasten by sash chain 2 required Media For Which Designed: Fuel/oil, hydrocarbon single response Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A542a0