NSN 4720-00-992-6832

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-992-6832

Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.750 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
1.250 inches				
Minimum Inside Bending Radius:				
9.500 inches				
Exterior Color:				
Black				
Connection Style:				
Inverted flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded external pipe 1st end				
Features Provided:				
Electrostatic discharge capability				
Burst Test Pressure:				
9000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
2250.0 pounds per square inch				
Thread Size:				
0.750 inches 1st end				
Seat Angle:				
30.0 degrees 1st end				
Hydrostatic Test Pressure:				
4500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Abrasion resistant and oil resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
43.000 inches				
Media For Which Designed:				
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response				

NSN 4720-00-992-6832

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0