Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-992-6837

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 11000.0 pounds per square inch
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Right-hand 1st endInside Diameter:0.250 inchesTempurature Rating:-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single responseOutside Diameter:0.625 inchesMinimum Inside Bending Radius:4.000 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:Threaded internal tube 1st endBurst Test Pressure:
Inside Diameter: 0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimun Inside Bending Radius: 4.000 inches Exterior Color: Black Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
0.250 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Outside Diameter: 0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
0.625 inches Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Minimum Inside Bending Radius: 4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
4.000 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Straight 2nd end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Threaded internal tube 1st end Burst Test Pressure:
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
5500.0 pounds per square inch
Inside Surface Condition:
Smooth
onoon
Measuring Method And Length:
Measuring Method And Length:
Measuring Method And Length: 32.000 inches
Measuring Method And Length: 32.000 inches Media For Which Designed:

NSN 4720-00-992-6837

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

