## NSN 4720-00-993-4282



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-993-4282 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.312 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.446 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** 

Swivel nut, flareless 1st end

**End Connection Design:** 

Straight 1st end

**Connection Type:** 

Threaded internal tube 1st end

**Burst Test Pressure:** 

9000.0 pounds per square inch

**Layer Composition And Location:** 

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:** 

1500.0 pounds per square inch

**Thread Size:** 

0.562 inches 1st end

Seat Angle:

12.0 degrees 1st end

**Hydrostatic Test Pressure:** 

3000.0 pounds per square inch

Vacuum In Torr:

50.8

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

10.000 inches working

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

## NSN 4720-00-993-4282

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0