

View Online at <https://aerobasegroup.com/nsn/4720-00-993-9629>

Cross Sectional Shape:

Round

Inside Diameter:

0.625 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.250 inches 1st end

Outside Diameter:

1.078 inches

Minimum Inside Bending Radius:

6.500 inches

Bolt Hole Quantity:

4 2nd end

Connection Style:

Raised 1st end

Bolt Hole Diameter:

0.750 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

1500.0 pounds per square inch

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

300.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and fuel/oil, hydrocarbon and fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0