

View Online at <https://aerobasegroup.com/nsn/4720-00-993-9630>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.812 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

6.000 inches 1st end

**Outside Diameter:**

2.219 inches

**Minimum Inside Bending Radius:**

13.250 inches

**Bolt Hole Quantity:**

4 2nd end

**Connection Style:**

Raised 1st end

**Bolt Hole Diameter:**

0.750 inches 1st end

**End Flange Construction:**

Solid 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Raised face flange 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

1400.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

350.0 pounds per square inch

**Hydrostatic Test Pressure:**

700.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

300.000 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon and fuel/oil, hydrocarbon and fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0