NSN 4720-00-994-9153

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-994-9153

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.203 inches
Minimum Inside Bending Radius:
7.380 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3200.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated fabric
Maximum Operating Pressure:
800.0 pounds per square inch
800.0 pounds per square inch Thread Size:
Thread Size:
Thread Size: 0.750 inches 2nd end
Thread Size: 0.750 inches 2nd end Seat Angle:
Thread Size: 0.750 inches 2nd end Seat Angle: 37.0 degrees 1st end
Thread Size: 0.750 inches 2nd end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
Thread Size: 0.750 inches 2nd end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 1600.0 pounds per square inch
Thread Size: 0.750 inches 2nd end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 1600.0 pounds per square inch Outer Covering Environmental Protection:

44.000 inches

Measuring Method And Length:

NSN 4720-00-994-9153

Nonmetallic Hose Assembly - Page 2 of 2



Media	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0