

View Online at <https://aerobasegroup.com/nsn/4720-00-995-1234>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

4.000 inches

**Quick Disconnect Size:**

4.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Connection Type:**

Internal quick disconnect 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

500.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer spirally laid rayon cord err-100

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Vacuum In Torr:**

508.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

594.000 inches and 606.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, buna-n

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0