NSN 4720-00-995-2700

Cross Sectional Shape:

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-995-2700

Rouna
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
0.750 inches
Inner Conveying Tube Style:
Annular close-pitch corrugated
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Identical ends
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch

6.000 inches

Corrosion resistant

Outer Covering Environmental Protection:

Measuring Method And Length:

NSN 4720-00-995-2700

Metallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	--------------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0