NSN 4720-00-995-6368

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-995-6368

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
1.750 inches
Minimum Inside Bending Radius:
11.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 12 1st end
12 1st end
12 1st end Burst Test Pressure:
12 1st end Burst Test Pressure: 2000.0 pounds per square inch
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location:
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure:
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size:
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle:
12 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 36.5 degrees and 37.5 degrees 1st end
Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 36.5 degrees and 37.5 degrees 1st end Hydrostatic Test Pressure:
Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 36.5 degrees and 37.5 degrees 1st end Hydrostatic Test Pressure: 1000.0 pounds per square inch
Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 36.5 degrees and 37.5 degrees 1st end Hydrostatic Test Pressure: 1000.0 pounds per square inch Inside Surface Condition:
Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 36.5 degrees and 37.5 degrees 1st end Hydrostatic Test Pressure: 1000.0 pounds per square inch Inside Surface Condition: Smooth
Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 36.5 degrees and 37.5 degrees 1st end Hydrostatic Test Pressure: 1000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length:

Un 1st end

Thread Series Designator:

NSN 4720-00-995-6368

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0